

Technical Data Sheet Linseed Oil Fatty Acid LAD 180-6

Quick Drying Fatty Acid Expert!

LAD 180-6 | Overview

Linseed Oil Fatty Acid (LOFA), its main content are linolenic acid, linoleic acid and oleic acid, as well as small amount of palmtic acid, and stearic acid.

HS code: 2916150000, CAS No.:68424-45-3

	Indicators	Typical Parameter	Test Method
Appearance	Light yellow Transparaent liquid	Light yellow Transparaent liquid	Visual Inspection
Color, Fe-Co method,#	€6	2+	GB/T 1722
Acid Value, mgKOH/g	195-205	201	GB/T 9104
Iodine Value, gl/100g	≥180	182	GB/T 5532
Frozen Point,°C,≤	≤18	17	SN/T 0801.17
Unsaponifiable Content, %	≤1	0.8	GB/T 5535.2

Features

High Iodine Value & High Reactivity

High Acid Value

Good Drying Properties

Good Anti-corrosion, High Adhesion, Good Fullness

Usages

- 1. For quick-drying coatings
- 2. For quick-drying printing inks
- 3. For resins like alkyd resin and epoxy ester resin

Packaging, Transport and Storage

- 1. Packages: IBC tank, plastic drum, ISO tanks or flex tanks.
- 2. Not hazardous, flammable, keep away from ignition sources.
- 3. Effective storage period of one year.

Anhui Refind Oil & Fat

No.19 Fenliu East Road, Langxi, Anhui Province, China

http://www.rfdyz.com/

Tel: 0563-2759808 Mobile: +86 15695636035 Email: <u>Charlie@rfdyz.com</u>